





**Pressmaßtabelle Kanalspülschlauch  
CRIMPING DIMENSIONS SEWER JETTING HOSE**

Empfohlene Pressmaße - Recommended Swaging Diameters

Ø Schlauch HOSE SIZE	Schlauch / HOSE EF308 Set DKR / BSP Female	Schlauch / HOSE EF308 Set AGR / BSP Male	Empfohlene Pressmaße	GO	NO GO
DN 12 1/2"	73-FGS0808 Ø 24,7 ± 0,1	73-MGS0808 Ø 24,7 ± 0,1			
DN 19 3/4"	73-FGS1212 Ø 31,6 ± 0,1	73-MGS1212 Ø 31,6 ± 0,1		Ø 7,7	Ø 8,8
DN 25 1"	73-FGS1616 Ø 40,3 ± 0,1	73-MGS1616 Ø 40,3 ± 0,1		Ø 11,5	Ø 13,0
DN 25 1"	73-FGSK1616 Ø 39,0 ± 0,1	73-MGSK1616 Ø 39,0 ± 0,1		Ø 17,5	Ø 18,5
DN 31 1.1/4"	73-FGS2020 Ø 48,8 ± 0,1	73-MGS2020 Ø 48,8 ± 0,1		Ø 16,2	Ø 18,4
				Ø 22,2	Ø 23,7



ACHTUNG: Armaturen für Kanalspülschlauch werden als SET bzw. Nippel und Fassung geliefert und Maß gepresst

ATTENTION: Fittings for Sewer Jetting hose are delivered in a SET of Insert and ferrule and swaged down to swaging diameter.

Alle Abmessungen in [mm] -  
All dimensions are in [mm] -

